

L1125

VENDED HARD-MOUNT WASHER-EXTRACTOR

PRODUCT SPECS

Capacity <i>lbs</i>	125
Cylinder Diameter <i>inch</i>	42.5
Cylinder Depth <i>inch</i>	23.5
Cylinder Volume <i>cu ft</i>	19.4
Net Weight <i>lbs</i>	2426
Crated Weight <i>lbs</i>	2734
Machine Dimensions <i>inch</i> WxDxH	56 x 55 x 69
Door Opening <i>inch</i>	21.6
Floor to Door <i>inch</i>	24.4 plus base
Shipping Dimensions <i>inch</i> WxDxH	60 x 59 x 77
Washing Speed <i>rpm</i>	34
Spin Speed <i>rpm</i>	465
G-force	130
Static Force Transmitted <i>lbs</i>	3080
Dynamic Force Transmitted <i>lbs</i>	5500
Frequency of Dynamic Force <i>Hz</i>	7.8
Available Voltages/Wire Conductor/Amp	208-240/60/3, 3W+G, 40 440/60/3, 3W+G, 25
Drain Diameter <i>inch</i>	3
Water Inlets <i>inch</i>	1
Recommended Water Pressure <i>PSI</i>	7-90
Water Flow <i>gal/min</i>	27
Total Power <i>kW</i>	3.5

Terminal Connections All Models		Chemical Injection (Dosing)
Supply #	Conn. #	PM Model Terminal Connections
5	X5-6	47
4	X5-5	46
3	X5-4	45
2	X5-3	44
1	X5-2	43
Common	X5-1	207

* Specifications subject to change without notice or obligation. Contact Continental Girbau at (800) 256-1073 for dimensions not shown or for clarification.

