


X13061 POSEIDON HEATED-ROLL IRONER

PRODUCT SE	PECS			
Cylinder Diameter <i>inch</i>		12.8		
Usable Cylinder Width <i>inch</i>		60.6		
Evaporation Ca	apability <i>gal/h</i>	3.96		
Ironing Speed ft/min		3-36		
Net Weight Ibs		1012		
Crated Weight <i>lbs</i>		1360		
Machine Width inch		91.1		
Machine Depth	inch	34.3		
Machine Heigh	t <i>inch</i>	55.7		
Feed Height inch		39.2		
Shipping Dimensions inch (WxDxH)		96.4 x 35.6 x 63		
Motor Power <i>Hp</i> Roller Motor Extraction Motor		0.40 0.40		
Exhaust Diameter inch		4.5		
Exhaust Air Flo Gas Electric	ow cfm	387 353		
Electric Heating 208/60/3 240/60/3	g <i>kW</i>	12.39 16.5		
Gas Connection inch		3/4 NPT		
Gas Heating <i>BTU/h</i> Natural Propane		79,844 76,773		
Gas Consumption <i>cfm</i> Natural Propane		1.46 3.78		
Gas Supply Pressure <i>inch wc</i> Natural Propane		7 11		
Circuit Protection Amps				
Gas Electric	208-240/60/1 208/60/3 240/60/3	10 70 70		
Full Load <i>Amps</i>				
Gas Electric	208-240/60/1 208/60/3 240/60/3	4.7 39 44		














^{*} Specifications subject to change without notice or obligation. Contact Poseidon Textile Care Systems at (800) 482-3400 for dimensions not shown or for clarification.

X13084 POSEIDON HEATED-ROLL IRONER

PRODUCT SPECS				
Cylinder Diameter <i>inch</i>	12.8			
Usable Cylinder Width inch	83.5			
Evaporation Capability gal/h	5.28			
Ironing Speed ft/min	3-36			
Net Weight Ibs	1237			
Crated Weight <i>lbs</i>	1630			
Machine Width inch	114			
Machine Depth inch	34.3			
Machine Height <i>inch</i>	55.7			
Feed Height inch	39.2			
Shipping Dimensions <i>inch</i> (WxDxH)	119.5 x 35.6 x 63			
Motor Power <i>Hp</i> Roller Motor Extraction Motor	0.40 0.40			
Exhaust Diameter <i>inch</i>	4.5			
Exhaust Air Flow <i>cfm</i> Gas Electric	387 353			
Electric Heating kW 208/60/3 240/60/3	17.44 23.22			
Gas Connection inch	3/4 NPT			
Gas Heating <i>BTU/h</i> Natural Propane	98,611 102,705			
Gas Consumption <i>cfm</i> Natural Propane	1.8 5.06			
Gas Supply Pressure <i>inch wc</i> Natural Propane	7 11			
Circuit Protection Amps				
Gas 208-240/60/1 Electric 208/60/3 240/60/3	10 80 80			
Full Load <i>Amps</i>				
Gas 208-240/60/1 Electric 208/60/3 240/60/3	4.7 53 61			














^{*} Specifications subject to change without notice or obligation. Contact Poseidon Textile Care Systems at (800) 482-3400 for dimensions not shown or for clarification.


X20075 POSEIDON HEATED-ROLL IRONER

PRODUCT SPE	CS	
Cylinder Diamete	r inch	20.1
Usable Cylinder V	74.8	
Evaporation Capability gal/h Gas/Electric Steam		7.93 11.1
Ironing Speed ft/	/min	4-49
Net Weight <i>lbs</i> Gas/Electric	without folder with folder	2282 2496
Steam	without folder with folder	2525 2739
Crated Weight <i>lb</i> Gas/Electric	s without folder with folder	2834 3080
Steam	without folder with folder	3076 3323
Machine Width <i>ir</i>	nch	111.7
Machine Depth in	nch	46.2
Machine Height i	nch	64.2
Feed Height inch		40.6
Shipping Dimension without folder with folder	ons (WxDxH) <i>inch</i>	117.6 × 45.5 × 71.9 117.6 × 50.6 × 71.9
Motor Power <i>Hp</i> Roller Motor Extraction Motor	or	0.40 0.74
Exhaust Diameter	inch	5.1
Exhaust Air Flow <i>cfm</i> Gas Electric/Steam		564 634
Electric Heating 208/60/3 240/60/3	kW	28.34 37.73
Gas Connection <i>inch</i>		3/4 NPT
Gas Heating <i>BTU</i> Natural Propane	1/h	163,100 158,323
Gas Consumption Natural Propane	cfm	2.98 7.81
Gas Pressure Oper Natural Propane	rating Manifold inch wc	7 11
Steam Connectio	n <i>inch</i>	1
Steam Condensat	te Outlet inch	3/4
Steam Heating B		166,513
Steam Consumption <i>lbs/h</i>		190
Steam Consumption <i>Ibs/n</i> Steam Pressure <i>PSI</i>		116
Safety Valve Con	1	
Gas/Steam : Electric	208-240/60/1 208/60/3 240/60/3	10 125 125
Full Load <i>Amps</i>		
Gas/Steam : Electric	208-240/60/1 208/60/3 240/60/3	6.1 85 97














^{*} Specifications subject to change without notice or obligation. Contact Poseidon Textile Care Systems at (800) 482-3400 for dimensions not shown or for clarification.


X20100 POSEIDON HEATED-ROLL IRONER

PRODUCT SPE	rs	
PRODUCT SPECS Cylinder Diameter inch		20.1
Usable Cylinder V		99.6
_		33.0
Evaporation Capability gal/h Gas/Electric Steam		10.57 14.79
Ironing Speed ft/min		4-49
Net Weight <i>lbs</i> Gas/Electric Steam	without folder with folder without folder	2788 3069 3031
	with folder	3312
Crated Weight Ib. Gas/Electric Steam		3439 3775 3681 4017
Machine Width <i>ir</i>		136.6
Machine Depth <i>ir</i>		46.2
Machine Height in		64.2
Feed Height <i>inch</i>		40.6
_	ons (WxDxH) inch	142.1 x 45.5 x 71.9 142.1 x 50.6 x 71.9
Motor Power <i>Hp</i> Roller Motor Extraction Moto	r	0.40 0.74
Exhaust Diameter <i>inch</i>		5.1
Exhaust Air Flow Gas Electric/Steam	cfm	564 634
Electric Heating 7 208/60/3 240/60/3	kW	37.06 49.34
Gas Connection i	inch	3/4 NPT
Gas Heating <i>BTU</i> , Natural Propane	/h	208,823 201,999
Gas Consumption Natural Propane	cfm	3.81 9.95
Gas Pressure Operating Manifold <i>inch wc</i> Natural Propane		7 11
Steam Connection	n <i>inch</i>	1
Steam Condensat	e Outlet inch	3/4 (19)
Steam Heating B		221,789
		254
Steam Consumption Ibs/h		116
Steam Pressure <i>PSI</i>		
Safety Valve Conr Circuit Protection		1
Gas/Steam 2 Electric	208-240/60/1 208/60/3 240/60/3	10 160 160
Full Load <i>Amps</i>		
Gas/Steam 2 Electric	208-240/60/1 208/60/3 240/60/3	6.1 109 125













^{*} Specifications subject to change without notice or obligation. Contact Poseidon Textile Care Systems at (800) 482-3400 for dimensions not shown or for clarification.


X20125 POSEIDON HEATED-ROLL IRONER


DDODUCT CDE	CS	
PRODUCT SPE	20.1	
Cylinder Diamete		20.1
Usable Cylinder Width <i>inch</i>		124.0
Evaporation Capability gal/h Gas Electric Steam		15.85 13.21 18.49
Ironing Speed ft/min		4-49
Net Weight Ibs		
Gas/Electric Steam	without folder with folder without folder with folder	3137 3497 3379 3739
Crated Weight <i>Ib</i> Gas/Electric	s without folder with folder	3876 4290
Steam	with folder with folder	4118 4533
Machine Width ir	nch	161.5
Machine Depth ir	nch	46.2
Machine Height i	nch	64.2
Feed Height inch		40.6
without folder with folder	ons (WxDxH) <i>inch</i>	167.3 x 45.5 x 71.9 167.3 x 50.6 x 71.9
Motor Power <i>Hp</i> Roller Motor Extraction Moto	or	0.40 0.74
Exhaust Diameter	inch	5.1 (130)
Exhaust Air Flow <i>cfm</i> Gas Electric/Steam		564 634
Electric Heating 7 208/60/3 240/60/3	kW	47.32 63
Gas Connection	inch	3/4 NPT
Gas Heating <i>BTU</i> Natural Propane	!/h	256,593 256,934
Gas Consumption Natural Propane	cfm	4.69 12.66
Gas Pressure Oper Natural Propane	ating Manifold inch wc	7 11
Steam Connection	n <i>inch</i>	1
Steam Condensat	e Outlet inch	3/4
Steam Heating <i>BTU/h</i>		277,748
Steam Consumption Ibs/h		317
Steam Pressure <i>PSI</i>		116
Safety Valve Connection <i>inch</i>		1
Circuit Protection	,	
	208-240/60/1 208/60/3 240/60/3	10 200 200
Full Load <i>Amps</i> Gas/Steam Electric	208-240/60/1 208/60/3 240/60/3	6.1 137 158





AREA NEEDED FOR SERVICE







^{*} Specifications subject to change without notice or obligation. Contact Poseidon Textile Care Systems at (800) 482-3400 for dimensions not shown or for clarification.